



EMS0007

Waste Management Plan

~~Australian Panels~~Products

124 Lowes Mount Road, Oberon NSW

~~Australian Panels~~Porta Products Pty Ltd

~~295 September~~November 2024~~2025~~

This document should be read in conjunction with EMS0060 Construction Environment Management Plan, EMS0001 Operational Environment Management Plan, EMS0006 Surface Water Management Plan, SEP Waste Storage Areas and SEP Stockpile Map

Revision History


Rev No.	Revision Date	Author	Comments	Details	Authorised	
					Name	Signature
0	24/11/17	Carly McCormack		Final	Victor Bendeviski	
1	02/11/18	Jacqueline Blomberg	Update 2.4 Environment Protection Licence condition L3 & L7	Review as per SSD7016 C10(d)	V Bendeviski	
1	07/12/18	J Blomberg	No updates necessary, remains as Rev. 1	Review as per SSD7016 C10(a) MOD 1 granted 20/11/18		
2	02/10/19	J Blomberg	Update Section 2.4 to include for EPL waste			
3	18/01/21	J Blomberg		Update as per SSD 7016 condition B52	V Bendeviski	
4	17/12/21	Andrew Brady		Update as per SSD 7016 condition B52	J Blomberg	
5	16/08/22	A Brady	Name change and inclusion of MOD 4	Update as per SSD 7016 condition C10 (a) & (c)	J Blomberg	
6	25/08/23	A Brady		Update as per SSD 7016 condition C10(c)	V Bendeviski	
7	5/09/24	A Brady	Name change and inclusion of MOD 5	Update as per SSD 7016 condition C10 (a) & (c)	A Brady	
<u>8</u>	<u>29/10/2025</u>	<u>A Brady</u>	<u>Name change, updates to waste quantities</u>	<u>Update as per SSD 7016 condition C10 (c)</u>	<u>A Brady</u>	

Table of Contents

1	Introduction	1
1.1	Background	1
1.2	Purpose and Objectives	1
1.3	Structure of this Waste Management Plan.....	2
1.4	Approval of the WMP	2
1.5	Training	2
2	Legislative and Regulatory Compliance.....	32
2.1	Relevant Legislation	32
2.2	Conditions of Consent	3
2.3	Development Consent SSD 7016 Mitigation Measures	5
2.4	Environment Protection Licence	65
3	Process Overview	8
3.1	MDF Plant	8
3.1.1	Waste Streams	8
3.1.2	Bark	8
3.1.3	Oversize and Undersize Woodchips	98
3.1.4	Fibre – Prior to Press Line.....	9
3.1.5	Fibre – Press Line	9
3.1.6	Reject Board	109
3.1.7	Sawdust and Sanding Belts	10
3.1.8	MDF Trim	10
3.1.9	Product Packaging	10
3.1.10	Heat Plant Ash	10
3.2	Particleboard	12
3.2.1	Waste Streams	12
3.2.2	Bark	12
3.2.3	Flaking	12
3.2.4	Dryer	12
3.2.5	Blending, Forming, Pressing	1243
3.2.6	Trimming, Sanding, Finishing.....	13
3.3	Mouldings Plant.....	13
3.3.1	General	13
3.3.2	Waste Streams	13
3.3.3	Plastic Strapping and Packaging from MDF Receival.....	1344
3.3.4	Product Trim and Offcuts	14
3.3.5	Sawdust	14

3.3.6	Paint, Paint Filters and Paint Washdown.....	14
3.3.7	Product Packaging.....	14
3.3.8	Reject Material	15
3.4	Paper Treater	17
3.4.1	General	17
3.4.2	Waste Streams	17
3.4.3	Raw Paper	17
3.4.4	Cardboard Cores	17
3.4.5	Waste Resin.....	17
3.4.6	Dried Treated Paper.....	17
3.4.7	Wet Treated Paper.....	17
3.5	Laminating Presses	18
3.5.1	General	18
3.5.2	Waste Streams	18
3.5.3	Dry Treated Paper.....	18
3.5.4	Reject Laminated Board.....	18
3.5.5	Plastic Film Wrapping	18
3.5.6	Packaging	18
3.7	Water Treatment Plant	18
3.7.1	General	18
3.7.2	Waste Streams	19
3.7.3	Chemical Containers.....	19
3.7.4	Brine	19
3.7.5	Solids from Filtration.....	19
3.8	Common Waste Streams	19
3.8.1	Scrap Metal	19
3.8.2	Waste Oil.....	19
3.8.3	Chemical Containers	19
3.8.4	General Waste	20
3.9	Waste Quantities	20
4	Implementation.....	21
4.1	Minimising Waste Production	21
4.2	Waste Hierarchy.....	21
4.3	Waste Monitoring	21
4.4	Management of Waste Streams	21
4.5	Waste Storage Areas	24
4.6	Waste Minimisation and Avoidance	24
4.7	Waste Receipt and Handling On-Site	24
5	Incidents and Complaints Management	24
5.1	Incidents.....	24
5.2	Complaints	24
5.3	Non-Compliances.....	24
5.4	Contingency Planning	25
6	Monitoring and Review	25
6.1	Inspections.....	25
6.2	Waste Tracking	25
6.3	Documentation and Record Keeping.....	25
6.4	Reporting.....	25
6.5	Review and Auditing of this Plan	26

1 Introduction

1.1 Background

~~This Management Plan has been prepared for the Porta Products Pty Ltd (Formally Borg Manufacturing, Borg Panels, Australian Panels) Oberon site (and will be referred to herein as the 'Development').~~

~~Borg Panels/ Borg Manufacturing Pty Ltd has recently undergone a name change to Australian Panels Pty Ltd and is in the process of updating all documentation and licenses to reflect this.~~

~~Australian Panels~~The Development operates as a medium density fibreboard (MDF) and particleboard facility in Oberon NSW manufacturing a range of Customwood MDF and particleboard products including:

- Standard MDF;
- Moisture Resistant MDF;
- E0 (Low Formaldehyde Emitting) MDF;
- Ultraprime MDF Mouldings;
- Standard particleboard;
- Moisture resistance particleboard;
- Particleboard flooring products for structural applications;
- Decorative Laminated MDF and particleboard; and
- Treated paper for the lamination of MDF and particleboard.

On 29 May 2017 Development Consent SSD 7016 was granted by the Minister for Planning to construct a Particle Board manufacturing facility, modify the existing MDF manufacturing facility and undertake general site works (the Project) at the existing ~~Australian Panels~~ facility located on 124 Lowes Mount Road, Oberon.

Conditions contained within the Consent require ~~Australian Panels~~Porta Products to provide for the ongoing environmental management of the Development. Though initially developed to satisfy conditions B51, C4 and C9, this Waste Management Plan has been updated to include for condition B52. Additionally, this WMP will be reviewed and updated as per SSD 7016 condition C10.

1.2 Purpose and Objectives

The purpose of this WMP is to provide the management and performance requirements related to waste at the ~~Australian Panels facility~~Development, and includes:

- Requirements for management of waste for operations at the facility as stipulated by regulatory approvals for the Development;
- Description of potential sources of wastes and risks related to waste management;
- Detail the 'waste' materials to be reused/recycled for production;
- Detail procedures for managing, handling and accepting the materials to be reused/recycled;
- Description of the environmental controls to meet objectives, and regulatory approval requirements; and

Formatted: Not Highlight

Formatted: Indent: Left: 0 cm

- Overview of the environmental monitoring programs associated with environmental controls and management actions.

The objectives of the WMP are to:

- Advise site personnel of their responsibilities in managing waste generated at the site;
- Advise site personnel of their responsibilities in managing, handling and accepting waste that will be reused on-site in the manufacturing process; and
- Ensure compliance with the conditions of approval related to waste management.

1.3 Structure of this Waste Management Plan

This WMP has been developed to manage waste generated by the facility and to satisfy the requirements set out in conditions of Development Consent SSD 7016, and includes information on the following:

- Section 2 – Legislative and Regulatory Compliance
- Section 3 – Process Overview
- Section 4 – Urban Wood Residue/Reuse Material
- Section 5 – Implementation
- Section 6 – Incidents and Complaints Management
- Section 7 – Monitoring and Review

1.4 Approval of the WMP

The WMP was submitted to the Secretary of the (then) Department of Planning and Environment (DP&E) on 30 November 2017. The Department reviewed the Plan and were satisfied it met the terms of the relevant conditions of consent. Accordingly, the WMP was approved by the Department on 21 December 2017.

Any subsequent versions of the WMP will be submitted to DPE for approval as per SSD 7016 Condition C10 as is necessary.

1.5 Training

Training and Assessment Manual EMS0020 Environmental Standard Awareness Waste has been developed for the site. This training will continue be delivered to all Supervisors and Operators on site. The Manual outlines ~~Australian Panels~~ employees responsibilities to assist with managing waste across the site and ensure ongoing regulatory compliance. The Training and Assessment Manual will be reviewed as necessary where site conditions change to ensure it accurately reflects site operations and training requirements.

Standard Operating Procedure EMS0030 Receiving and Accepting Urban Wood Residue (UWR) has been developed for site. This is to ensure the type and quality of UWR received on site which is to be incorporated into new particleboard meets ~~Berg~~ specification, EPA licence and Development Consent conditions, and NSW Government Regulations.

All training records are maintained in DataStation.

2 Legislative and Regulatory Compliance

2.1 Relevant Legislation

Key environmental legislation relating to waste management for the facility includes:

- *Protection of the Environment Operations Act 1997*;
- Protection of the Environment Operations (Waste) Regulation 2014; and
- *Waste Avoidance and Resource Recovery Act 2001*.

2.2 Conditions of Consent

The operations at ~~the Development Australian Panels~~ are subject to the conditions contained in Development Consent SSD 7016 and the following modifications:

- MOD 1 – extension of mouldings warehouse, reorientation of materials handling building, layout change to particleboard chipper/debarker building, extension of northern noise bund, reconfiguration of elements of the surface water management system, reclamation of the Spring Dam (approved 20 November 2018)
- MOD 2 – installation of an electricity generation gas turbine and ancillary equipment (approved 29 November 2019)
- MOD 3 – additional materials handling equipment, extension to northern warehouse, changes to the site surface water system and construction of further hardstand
- MOD 4 – Additions and alterations to the existing timber processing facility including reclamation of the remaining spring fed dam, relocation and expansion of the existing mechanic's workshop and improvements to the site's water treatment plant (approved 20 August 2022)
- MOD 5 – Minor update to the approved mechanical workshop including additional workshop bays, additional first floor storage and minor updates to the office plus removal of the refuelling system and automated truck washing machine. The proposed development will also result in the increase in length of the stormwater management system to cover an additional 11m length of the mechanics workshop building. (approved 23 April 2024)

For each of the above modifications, the Minister did not impose any additional conditions specific to this Management Plan.

The specific requirements for a WMP (Schedule 2, Condition B51 and B52) and general requirements for environmental management plans (Schedule 2, Condition C9) are detailed in ~~Table 1~~~~Table 4~~.

Formatted: Font: 11 pt

Table 1 - Development Consent Conditions

No.	Requirement	Document Reference
	WASTE MANAGEMENT	
	Waste Management Plan	
B51.	Within 6 months of the date of this consent, the Applicant must prepare a Waste Management Plan (WMP) for the Existing Development to the satisfaction of the Secretary. The WMP must form part of the OEMP required by Condition C4 and be prepared in accordance with Condition C9. The WMP must:	This Plan
	a) detail the type and quantity of waste generated by the Existing Development;	Section 3
	b) describe the handling, storage and disposal of all waste streams generated on site, consistent with the POEO Act, <i>Protection of the Environment Operations (Waste) Regulation 2014</i> and the <i>Waste Classification Guideline</i> (Department of Environment, Climate Change and Water, 2009);	Section 4
	c) detail the materials that are being reused or recycled, either on or off site; and	Section 4
	d) include the Management and Mitigation Measures included in Appendix B.	Section 2.3
B52	Prior to commencement of operation of the Project, the Applicant must update the WMP required under Condition B51 to incorporate the Project and its management to the satisfaction of the Secretary. The updated plan must be prepared in accordance with the requirements of Condition B51, and must incorporate the following:	This Plan
	(a) details of the materials to be reused and recycled for the Project; and	Section 4
	(b) details of the procedures for managing, handling and accepting materials to be reused or recycled on-site for the Project.	Section 4
	MANAGEMENT PLAN REQUIREMENTS	
C9	The Applicant must ensure that the environmental management plans required under Condition C4 of this consent are prepared by a suitably qualified person or persons in accordance with best practice and include:	Revision History
	a) detailed baseline data;	Section 3
	b) a description of: (i) the relevant statutory requirements (including any relevant approval, licence or lease conditions); (ii) any relevant limits or performance measures/criteria; and (iii) the specific performance indicators that are proposed to be used to judge the performance of, or guide the implementation of, the Development or any management measures;	Section 2

No.	Requirement	Document Reference
	c) a description of the management measures that would be implemented to comply with the relevant statutory requirements, limits or performance measures/criteria;	Section 4
	d) a program to monitor and report on the: (i) impacts and environmental performance of the Development; and (ii) effectiveness of any management measures (see (c) above);	Section 6
	e) a contingency plan to manage any unpredicted impacts and their consequences;	Section 5.4
	f) a program to investigate and implement ways to improve the environmental performance of the Development over time;	Section 4.3
	g) a protocol for managing and reporting any: (i) incidents; (ii) complaints; (iii) non-compliances with statutory requirements; and (iv) exceedances of the impact assessment criteria and/or performance criteria; and	Section 5
	h) a protocol for periodic review of the plan.	Section 6.5
	Note: <i>These requirements also apply to the preparation or updates of management plans for the Existing Development and the Project.</i>	

2.3 Development Consent SSD 7016 Mitigation Measures

Appendix B Applicant's Management and Mitigation Measures to Development Consent SSD 7016 details the reasonable and practical measures to avoid or minimise impacts to the environment that may arise as a result of the Project. The following is included for waste:

Recovered Wood Material/Products

EPA approval will be obtained prior to the use of recycled materials in the particleboard manufacturing process.

In 2019-2020, ~~Australian Panels~~~~the Development~~ undertook an EPA approved trial for the receipt, storage, processing and use of urban wood residue (UWR) as an alternative raw material to be used in the production of particleboard. Upon successful completion of the trial, ~~Australian Panels the Development~~ applied to the EPA for a site specific resource recovery order and exemption to allow for the continued use of UWR in the manufacture of particleboard. The EPA issued ~~Porta Products~~~~Australian Panels~~ with ~~The Borg Panels Urban Wood Residue order March 2021~~ and ~~The Borg Panels Urban Wood Residue exemption March 2021~~.

Formatted: Font: Italic

Formatted: Font: Italic

In 2021 ~~Australian Panels~~~~the Development~~ applied to the EPA for a second trial for the acceptance of resource recovered engineered wood products for use in the manufacture of particleboard. Special Condition E1 was applied to EPL 3035 for this trial. This trial was approved to run within a period of 12 months. Following conclusion of this trial, ~~Australian~~

~~Panel~~the Development prepared and submitted to the EPA a report on the findings of the trial.

2.4 Environment Protection Licence

Environment Protection Licence 3035 (EPL 3035) specifies waste that may be received at the premises and use of that waste during operation of the facility.

Condition L3 Waste of EPL 3035 states:

L3.1 The licensee must not cause, permit or allow any waste to be received at the premises, except the wastes expressly referred to in the column titled "Waste" and meeting the definition, if any, in the column titled "Description" in the table below.

Any waste received at the premises must only be used for the activities referred to in relation to that waste in the column titled "Activity" in the table below.

Any waste received at the premises is subject to those limits or conditions, if any, referred to in relation to that waste contained in the column titled "Other Limits" in the table below.

This condition does not limit any other conditions in this licence.

Code	Waste	Description	Activity	Other Limits
NA	General or Specific exempted waste	Borg Panels Urban Wood Residue that meets all the conditions of The Borg Urban Wood Residue Order March 2021 under Part 9 Clause 93 of the Protection of the Environment Operations (Waste) regulation 2014	As specified in each particular resource recovery exemption	Maximum 200,000 tonnes of UWR per annum and no more than 40,000 tonnes at any one time.
NA	General or Specific exempted waste	Soil that meets all the conditions of the Sydney Trains screened soil order under Part 9 Clause 93 of the Protection of the Environment Operations (Waste) regulation 2014	As specified in each particular resource recovery exemption	NA
NA	General or Specific exempted waste	Reclaimed Asphalt, that meets all the conditions of the reclaimed asphalt pavement order under Part 9 Clause 93 of the POEO (Waste) Regulation 2014	As specified in each particular resource recovery exemption	NA

Code	Waste	Description	Activity	Other Limits
NA	General or Specific exempted waste	Waste glass, that meets all the conditions of the recovered glass sand order under Part 9 Clause 93 of the POEO (Waste) Regulation 2014	As specified in each particular resource recovery exemption	NA
NA	General or Specific exempted waste	Waste ceramic tiles, sourced from National Ceramic Industries Australia Pty Limited, Rutherford NSW, that meets all the conditions of the recovered aggregate resource recovery order under Clauses 91-96 of the POEO (Waste) Regulation 2014	As specified in each particular resource recovery exemption	NA
NA	Non-standard Fuel sourced from materials generated within the Oberon Timber Complex	As defined in condition L7.2		Used in accordance with conditions L7.1 and L7.2
NA	Non-standard Fuel generated offsite from material originally manufactured within the Oberon Timber Complex	As defined in Condition L7.2		Used in accordance with conditions L7.1 and L7.2

Note: For the purposes of condition L3.1, the Oberon Timber Complex refers to the businesses known as Structaflor, ~~Highland Pine Products~~AKD, ~~Australian Panels~~Porta Products and Woodchem.

Condition L7 Other limit conditions of EPL 3035 states:

L7.1 Only the following materials may be used as fuel within the Conti 1 and Conti 2 heat plants: -

- a) Standard Fuel; and
- b) Non-Standard Fuel.

L7.2 For the purposes of condition L7.1, Non-Standard Fuels are those fuels that have been assessed by the EPA as being appropriate for use as a fuel additive and comprise those materials that are derived from Oberon Timber Complex activities. Non-Standard Fuels currently approved for use are: -

- a) MDF Board;
- b) Particle Board sourced from ~~Australian Panels~~Porta Products and Structaflor premises;
- b) Shredded MDF Board;
- c) Sander Dust;
- d) Laminated MDF Board;

- e) Water Treatment Plant sludge; and
- f) Saw dust/off-cuts sourced from Bearers 4 U Pty Limited (Lot 4 Albion Street, Oberon)

Licence version date 2 February 2022 includes section 8 Special Conditions that are specific to the second urban wood residue trial. Condition E1 Trial of Urban Wood Residue – Particleboard Factory includes (but not limited to) the following:

The licensee must undertake a trial of the receipt, storage processing and use of Urban Wood Residue (UWR) as an alternative raw material to be used at the particleboard factory within the premises (Trial 2). Trial 2 is to be conducted within a period of 12 months and conclude on 24 December 2022.

All UWR received at the premises must be managed in accordance with the Urban Wood Residue Quality Assurance and Control Plan, v2.0 (UWR QA/QC Plan).

The condition also outlines requirements for sampling and testing of the material, and the preparation of a Report following the conclusion of the trial.

3 Process Overview

3.1 MDF Plant

The MDF plant produces medium density fibreboard from the compression and densification of wood fibres treated with Melamine/Urea Formaldehyde polymer and wax. The MDF plant operates with two fully automated press lines producing boards of various dimensions. Product from the MDF plant is also used in the mouldings plant.

There are two heat plants (HP) in operation supplying heat to the facility. Fuel from the heat plants is sourced from both raw materials purchased for the plants and waste products obtained in accordance with EPL 3035 requirements (Section 2.4).

A schematic overview of the MDF process is shown in Figure 1.

3.1.1 Waste Streams

The following waste streams are generated in the MDF plant:

- Bark;
- Oversize and undersize wood chips;
- Fibre;
- Off-spec product / reject board;
- Sawdust and sanding belts;
- MDF trim;
- Packaging materials; and
- Heat plant ash.

3.1.2 Bark

Sorted logs are transferred to a debarking plant either directly from incoming trucks or from the log yard. Bark from this process falls to a lower deck and is collected by a scraper, which feeds the bark to a conveyor and stockpile.

Bark and other log wood refuse is then used as fuel for the heat plant or on-sold for landscaping purposes.

3.1.3 Oversize and Undersize Woodchips

De-barked logs are fed into a chipper, which converts the full log into a standard size chip suitable for further processing. The created chip is then fed by conveyor onto the chip piles. Chips are stored in large chip piles that utilise horizontal screw reclaimers at the base of the piles to feed chips into the refining process. Chips are screened and washed prior to the refining process to remove any oversize or undersize chip fractions and any stones, metal, or dirt that may cause process disruptions or flaws in the finished product. Undersize and oversize ~~chip~~chip that is unable to be reprocessed is collected and fed as fuel to the MDF heat plants.

3.1.4 Fibre – Prior to Press Line

Following washing, dewatered chips are refined into fibre. Fibre is produced by passing wood chip through a defibrator, a steam pressurised disk refinement process. The fibre produced is light and fine, which means it is easily spread by wind.

Wax and resin are added to the fibres before the fibre drying process. Wax is added to improve the moisture resistance of the board, and resin is added as an adhesive for the MDF board pressing process.

Process disruptions during start-up or fibre production can lead to a 'fibre dump' from the dryer start-up cyclone. Dumped fibre is collected in designated fibre dump pits located in the outdoor MDF plant area. The quantity of fibre dumped is not officially recorded either manually or automatically as part of the process control system. The size of the fibre 'dump' varies according to whether the dump is due to process start-up and shut-down or process disruptions.

The fibre dumps are generally constructed with three surrounding walls and an open front to allow collection of the fibre by a front-end loader. This design provides some protection from the risk of windblown fibre spreading throughout the plant.

Additionally, a street sweeper operates on a full-time basis to collect and control the spread of fibre across the outside areas of the MDF plant, and subsequently the spread of windblown fibre to other areas of the timber complex and surrounding properties. Fibre collected by the street sweeper is placed in the fibre dumps.

Fibre from the fibre dumps is taken to the fuel storage and mixing bunker at the MDF plant for blending with other approved fuels for use in the MDF heat plants.

Loose fibres from within enclosed buildings of the MDF plant are collected with a vacuum, which is also emptied into the fibre dumps.

3.1.5 Fibre – Press Line

Ensuring the fibre matt is of appropriate quality and thickness is essential to achieving the required finished product standard. Therefore, the fibre quality is subject to online analysis following the pre-press. If unsatisfactory, the load of fibre on the conveyor can be 'dumped' prior to entering the press.

The edges of the pre-pressed matt are trimmed to provide a clean edge prior to the main press. Trimmed fibre is recycled back into the process, with return to fibre storage prior to the

pre-press. There is no online analysis of the flowrate of fibre back into the process from the pre-press, or of reject fibre to the fibre dumps.

3.1.6 Reject Board

The quality of MDF exiting the main press is analysed online, with board that fails to meet the required standard being rejected prior to entering the star cooling wheel. The quantity of reject board from Conti 1, Conti 2 and Conti 4 press lines is recorded in the daily operations reports.

Board can also be rejected at later stages of the process by visual inspection. Board can be rejected from the production line by operators following sanding and trimming, and prior to packaging.

Rejected board from the press-line and later production stages is stockpiled for later use, predominantly as product packaging bearers. Leftovers and offcuts from the bearer making process are used as fuel in the MDF heat plants.

3.1.7 Sawdust and Sanding Belts

Following cooling and storage, MDF is sanded down to the required thickness and finish. Sawdust from the sanding process is collected under vacuum to a baghouse filter, prior to being blown across to sawdust storage silos at the MDF heat plants.

Sanding belts are approximately 2.65m x 2.8m and come packaged in large cardboard boxes. Approximately 1 belt per head requires changing each 12-hour shift. There are two thicknesses of finishing heads. Both the sanding belts and their cardboard packaging are disposed of as general waste to landfill.

3.1.8 MDF Trim

MDF is cut to the required size boards according to different product requirements. Trim offcuts can vary according to the product being produced. Wood trim from the trim saws (both the length and width cut) is automatically dropped onto a conveyor belt and fed to a wood hogger. The board is crushed and broken into smaller pieces in the hogger, which is then blown across to the fuel storage and mixing bunker for the MDF heat plants.

3.1.9 Product Packaging

MDF products are packaged using wood bearers, plastic strapping and plastic shrink wrap. All packaging wastes are disposed of as general mixed waste to landfill.

The plastic strap used in the MDF plant is recyclable, where possible it is segregated and reused however there is no segregated collection of plastic strap for recycling at the local waste facility so all additional strap waste is disposed of as general mixed waste to landfill.
~~the MDF plant.~~

3.1.10 Heat Plant Ash

Ash is the main waste stream from the heat plant. Ash is currently disposed of to landfill.

Formatted: Font: 13 pt

Formatted: Font: 13 pt, Bold




Figure 1 – Schematic Overview of the MDF Production Process

3.2 Particleboard

Particleboard manufacturing involves both the processing of virgin wood, residual wood waste from sawmills and the recycling and processing of appropriate used wood (UWR) to create suitable sized particles. These particles are blended with glue and a blend of urea formaldehyde with a paraffin wax emulsion. After blending, the particles are sent to the appropriate mat forming stations. The mat is then conveyed to the press via the forming line. The forming line is able to reject and recycle mat before pressing. Any reject material is reused on the site. Once processed, the board is cut, cooled and sanded, then stored for shipping.

3.2.1 Waste Streams

Waste streams generated from the manufacturing of particleboard include the following:

- Bark;
- Oversized and undersized wood chips;
- Off-spec product/board reject;
- Sawdust and sanding belts;
- Particleboard trim;
- Packaging materials; and
- WESP waste material.

3.2.2 Bark

Plantation timber logs are brought to site from external locations and processed through the timber yard. This includes processing the timber through a debarker and chipper. This chip is then fed on a covered conveyor to the chip storage silos (x2). Any fallen chip is swept up and added to the stockpile in the silos or taken to the fuel storage area.

3.2.3 Flaking

Chips are moved from the silos via covered belts and conveyors to the knife ring flakers designed to produce the optimum macro sized particles for processing. Saw dust is also introduced to the particles at this point. The flakers are located within an enclosed building. Any dust/small particles deposited outside the ring flaker are manually swept up and either used to fuel the heat plants or reintroduced into the particleboard production system.

3.2.4 Dryer

The dry saw dust and wet wood particles are then dried in a fully enclosed rotating drum drier. Any small particles generated during the drying process which are smaller than required are removed using cyclone extractors. Any surplus air generated which is not required for the drying process is cleaned using a Wet Electrostatic Precipitator (WESP) prior to being released to the atmosphere as clean air. Once dry and processed in this manner, the particles are removed and stored in a third silo.

Once this process has been carried out, screening is undertaken with any appropriately sized particles and dust sent to storage. Any oversized particles are sent to the grinding mill to reduce them to an appropriate size.

Dump chutes similar to those described in section 3.1.4 Fibre – Prior to Press Line are located in this area and waste from these are managed in the same way.

3.2.5 Blending, Forming, Pressing

Particles are then blended with glue and additives including urea formaldehyde and paraffin wax emulsions and sent to the mat forming stations. The forming stations ensure that there is

an even distribution of particles across both the width and thickness of the board. The mat is weighed and adjusted to ensure the finished product has a consistent density. Any reject mat is returned to the flaking system and reintroduced into the manufacturing process.

The forming line then transports the layered mat in a continuous format to the press. The forming line is able to reject and recycle the mat before pressing if the specified product parameters are not of a suitable standard. Any rejected material is reused on site. The press then applies the specified heat and pressure to cure and consolidate the board to meet or exceed Australian Standards.

3.2.6 Trimming, Sanding, Finishing

Once processed, the pressed board is then square cut, cooled and stored in an automated storage system. Any off cuts are put back through the system to create particleboard.

Once cooled and cured, the boards are removed from storage and processed through the sander to ensure they meet final standards. Sawdust from the sanding process is manually swept up by a mechanical sweeper for reuse on site.

Product packaging for particleboard is the same as for MDF described in section 3.1.9 above.

3.3 Mouldings Plant

3.3.1 General

The mouldings plant processes MDF sheets into finished (painted) mouldings suitable for use as skirting boards, doorjambs and architraves.

The main input materials to the mouldings process include MDF sheets from the MDF plant, paint, plastic wrap and strapping used in the final product packaging.

MDF sheets are cut to the required size using a multi-saw, prior to moulding and sanding to the required style and shape. The mouldings undergo a two stage (two coat) painting process with drying and intermediate de-nibbing (rubbing down) between paint stages, prior to visual inspection of the product, packaging, storage and delivery of product to markets.

A schematic overview of the mouldings process is shown in Figure 2.

3.3.2 Waste Streams

The following waste streams are generated in the mouldings plant:

- Plastic strapping and packaging from MDF receival;
- Product trim and offcuts;
- Sawdust;
- Paint, paint filters, and paint washdown;
- Product packaging; and
- Reject material.

3.3.3 Plastic Strapping and Packaging from MDF Receival

MDF sheets delivered to the mouldings plant are stacked on wood bearers supported with plastic strapping and are labelled.

The plastic strapping removed from the MDF is recyclable, however there is no segregated collection of plastic strap for recycling at the mouldings plant. MDF labels (equivalent to a printed A4 sheet) are disposed of as general waste.

Wood bearers are reused wherever possible. Undamaged wood bearers are returned to the MDF plant for reuse. Damaged wood bearers are collected and sent to the heat plants for use as fuel.

3.3.4 Product Trim and Offcuts

MDF offcuts from the initial sawing process are collected and sent to the MDF heat plants for use as fuel. The number of offcuts is dependent on the product specification and size of MDF board.

3.3.5 Sawdust

Sawdust from the sawing line, moulder, and sander is collected under vacuum to a baghouse filter, prior to being blown across to sawdust storage silos at the MDF heat plants.

Material removed from the painted timber surface in the denibbing process (following the first painting stage) is collected under vacuum to a baghouse filter, prior to being blown across to sawdust storage silos at the MDF heat plants.

Sawdust is also used to clean up any paint spillages. Paint soaked sawdust is dried and disposed of to a suitable landfill location.

3.3.6 Paint, Paint Filters and Paint Washdown

Painting is undertaken in a bunded area, allowing for cleaning and washdown of each painting area. The area is cleaned using water, and the washdown water is recycled back into the process via mixing with fresh paint in the paint day-tank or is sent to the water treatment plant for treatment. Contaminated paint waste is mixed with a polymer to form a spade-able waste which is taken to landfill.

Paint filters are cleaned and reused as required.

3.3.7 Product Packaging

Waste streams generated from the packaging line include:

- Cardboard boxes (received from delivery of packaging materials);
- Cardboard cores from rolls of plastic wrap;
- Damaged wood bearers;
- Plastic wrap; and
- Plastic strapping offcuts from the strapping machine.

Finished mouldings are stacked on laminated wooden bearers prior to strapping and covering with plastic wrap. Plastic wrap used in the wrapper is coiled over a cardboard core that is currently not returnable to the manufacturer, thus the cores are disposed of as general waste to landfill.

Bearers used to support mouldings products are made from MDF or untreated wood, therefore they are suitable for use as fuel in the MDF heat plants. Attempts are made to repair and reuse damaged wood bearers as much as possible. Broken bearers are used for fuel in the MDF heat plants.

3.3.8 Reject Material

Product is subject to visual inspection following application of the second coat of paint and prior to packaging. Product that fails to meet the required quality standard is removed from the process and recorded as reject. Rejected product is stockpiled for use as fuel in heat plants.




Figure 2 – Schematic Overview of the Mouldings Production Process

3.4 Paper Treater

3.4.1 General

The paper treater manufactures resin treated paper films that are used to laminate onto the surface of the MDF and particle board sheets. These films provide colour, texture and durability to the surface of the board.

The paper treatment process uses urea and melamine formaldehyde adhesives which are saturated into and onto a continuous paper web. The resin filled paper web is dried sufficiently, in gas fired flotation ovens, until they no longer tack together when placed in contact with one another.

The continuous web is then cut into suitable sized sheets or reeled onto a core for use on a continuous laminating press line.

3.4.2 Waste Streams

Waste streams generated from the paper treatment process include the following items:

- Raw paper;
- Cardboard cores;
- Waste resin;
- Dried treated paper; and
- Wet treated paper.

3.4.3 Raw Paper

The dense cardboard protective outer wrapping of the paper rolls is removed prior to preparation for the paper treatment process. Additionally, some of the decorative raw paper is also recycled or sent to the MDF heat plants to be used as fuel.

3.4.4 Cardboard Cores

Raw decorative paper is coiled over a cardboard core. Used cardboard cores are disposed of as general waste to landfill.

3.4.5 Waste Resin

Waste resin is generated at the end of a production run, or when there are process upsets to out of specification resin. End of run material can be pH stabilised and utilised during the next suitable production run. Out of specification material can be reused in the MDF board making process if the opportunity exists, otherwise it is chemically set to solidify and disposed of to landfill.

3.4.6 Dried Treated Paper

Dried treated paper is generated in process upset conditions when the continuous web is broken. This paper is very brittle and has no alternative uses and is therefore sent to landfill.

3.4.7 Wet Treated Paper

Wet treated paper is generated in process upset conditions when the continuous web is broken. This wet paper has no alternative uses and is also sent to landfill.

3.5 Laminating Presses

3.5.1 General

Laminating presses are used to thermally fuse the treated paper to the surface of the MDF and particleboard substrate. They operate by applying heat and pressure to the treated paper leaf and board assembly, which activates the glue causing it flow and bond to the surface of the board product.

3.5.2 Waste Streams

Waste streams generated from the laminating press process include the following:

- Dry treated paper;
- Reject laminated board;
- Plastic film from wrapping; and
- Packaging.

3.5.3 Dry Treated Paper

Dry treated paper that is broken or damaged during setup of the laminating process is sent to landfill.

3.5.4 Reject Laminated Board

Board that is not suitable for resale after the laminating process is generally reused by sanding and then re-laminated into A grade product. Alternatively, the board product is used in the bearer making process. Offcuts from the bearer making process are used onsite as fuel in heat plants.

3.5.5 Plastic Film Wrapping

Plastic film is used for wrapping treated paper to prevent moisture ingress. Used plastic film is sent to landfill.

3.5.6 Packaging

Treated paper is transported for use at other manufacturing sites in flat sheets. The paper sheets are protected with thick MDF top and bottom. Treated paper for use onsite is rolled onto aluminium cores.

Both the MDF used for transport and aluminium cores used onsite are reused in the same process until end of life, at which time the MDF is sent to the heat plants for fuel and aluminium cores are recycled.

3.7 Water Treatment Plant

3.7.1 General

The on-site water treatment plant processes all the effluent (process water) generated from various activities at site. The water treatment plant utilises filtration and biological degradation to remove contaminants from the water for re-use, capturing over 400KL per day from the site and reusing it in the manufacturing process.

More detail on the function and operation of the water treatment plant is provided in EMS0006 Surface Water Management Plan.

3.7.2 Waste Streams

Waste streams generated from operation of the water treatment plant include the following:

- Chemical containers;
- Brine; and
- Solids from filtration.

3.7.3 Chemical Containers

The water treatment plant requires chemicals for its operation, the chemicals are generally supplied in IBCs or bags for solid materials. Management of IBCs on-site is detailed in Section 3.6.3. Empty bags are disposed of to landfill.

3.7.4 Brine

The water treatment plant produces brine, a waste product from the Reverse Osmosis (RO) system, which is high in dissolved solids. Brine solids are currently treated within the water treatment plant by way of dilution then reused in the manufacturing process.

3.7.5 Solids from Filtration

Dewatered waste sludge (biomass) from the centrifuge is sent to the heat plant as fuel for the furnace.

3.8 Common Waste Streams

The following waste streams are common to more than one process on-site, and are handled, processed and recorded collectively for the facility.

3.8.1 Scrap Metal

Scrap metal with potential for reuse within the plant is stockpiled on site and reused wherever possible.

Other scrap metal that is not stockpiled is placed in scrap metal skip bins for removal from site to a metal recycler.

3.8.2 Waste Oil

Waste oil is collected from site for recycling by Cleanaway.

3.8.3 Chemical Containers

Empty chemical containers (IBCs) are washed and stored on-site prior to recycling, reuse or disposal. The majority of IBC's are reused at site, with the remainder that are not re-purposed or are at end of life being cut up or crushed and sent to landfill.

Waste drums of metal construction are triple rinsed and sent to the recyclers.

Waste requiring burial is made up of urea formaldehyde spade-able resin and paraffin wax bladders. Quantities of these are sporadic and disposal of resin in this manner is considered as a last resort as the product has a high capital cost. This waste is disposed of to Bathurst Regional Council Waste Management Centre.

3.8.4 General Waste

All general waste from work areas, offices and staff amenities is collected in bulk skip bins and taken to Oberon Council Waste Depot for disposal. There is no segregation of recyclable materials.

3.9 Waste Quantities

A summary of estimated waste generation at the ~~Australian Panels~~ facility is provided in ~~Table 2~~Table-2.

Formatted: Font: 11 pt

Table 2 – Summary of Waste Generated in ~~Australian Panels~~Porta Products Facility

Waste Stream	Estimated Annual Waste Generation	Disposal / End Use
Bark	30,000 tonnes	Fuel in heat plants plant or on-sold for landscaping purposes
Oversize and undersize woodchips	190,000 tonnes	particleboard manufacturing
Fibre	Not recorded	Fuel in heat plants or particleboard manufacturing
Reject Product	2,200 tonnes (assumed plants average density of 730kg/m ³)	Fuel in heat plants or particleboard manufacturing
Ash	2,255,750 m ³	Landfill
Sawdust	9,000 tonnes	particleboard manufacturing
Trim and Offcuts	7,000 tonnes	Fuel in heat plants or particleboard manufacturing
Wood Bearers	Included in MDF trim and offcuts	Fuel in heat plants
Scrap Metal	Not recorded <u>approximately 2,000 tonnes</u>	Recycled
Waste Oil	3040 ,000 litres	Recycled
Oil Drums	500 drums	Reused or returned
General Mixed Waste (sanding belts, cardboard, plastic strapping, shrink wrap, labels, paint filters, treated paper, general waste)	7,000 m ³	Landfill
Brine (from WTP)	100% reuse captured in board production	Reuse
Sludge (from WTP)	Not recorded	Fuel in heat plants
Chemical Containers (IBCs)	Included in general mixed waste	Reuse, recycle and landfill

Waste Stream	Estimated Annual Waste Generation	Disposal / End Use
Waste resin (spade-able or solidified) and paraffin wax bladders	150 tonnes	Bathurst Council Waste Management Centre – waste requiring burial

4 Implementation

4.1 Minimising Waste Production

~~Australian Panels~~ **The Development** aims to appropriately manage and minimise waste generation at the Oberon facility, including domestic waste production and the reuse and recycling of waste where possible.

4.2 Waste Hierarchy

~~The Development Australian Panels~~ will endeavour to manage the waste generated on site by following the best practices as set out in the *Waste Avoidance and Resource Recovery Act 2001*. The Waste Hierarchy of Control is detailed in Figure 3.




Figure 3 – Waste Hierarchy of Control

Waste is separated on site into different classes in accordance with the NSW EPA *Waste Classification Guidelines*. Before waste is removed from site it is assessed for suitability for the intended destination. Waste is classified into the groups identified in ~~Table 3~~ **Table 3**.

Formatted: Font: 11 pt

4.3 Waste Monitoring

Waste monitoring is undertaken at a corporate level. The focus of the monitoring program is to investigate and implement ways to reduce waste generation and increase recycling opportunities of the facility

4.4 Management of Waste Streams

Waste produced at the site is disposed of either by ~~Australian Panels~~ staff or licenced contractors to licenced waste facilities. The classification, management and disposal of wastes is outlined in ~~Table 3~~ **Table 3**.

Formatted: Font: 11 pt

Table 3 – Waste Classification, Management and Disposal

Waste Category	Source	Management	Disposal
General solid waste (putrescible)	Food scraps and wrappers from site personnel	No separation from general solid waste (non-putrescible)	Off-site disposal at Oberon Council Licenced Waste Facility
General solid waste (non-putrescible)	Sanding belts	Collected in skip bins	Off-site disposal at Oberon Council Licenced Waste Facility
	Heat plant ash	Stockpiled and disposed of to landfill as general waste	Off-site disposal at Oberon Council Licenced Waste Facility
	Paint solids, filters, spillages and linings	Dried and disposed of to landfill as general waste	Off-site disposal at Oberon Council Licenced Waste Facility
	Plastic strapping and wrapping	Collected in skip bins	Off-site disposal at Oberon Council Licenced Waste Facility
	Cardboard cores and cardboard boxes	Collected in skip bins	Off-site disposal at Oberon Council Licenced Waste Facility
	Treated paper	Collected in skip bins	Off-site disposal at Oberon Council Licenced Waste Facility
	Waste resin (spade-able or solidified) and paraffin wax bladders	Collected in skip bins	Bathurst Council Waste Management Centre – Waste requiring burial
General solid waste (recyclable)	Bark, oversize and undersize woodchip, fibre, sawdust, wood trim, bearers and reject product	Stored on site	Fuel in heat plants or particleboard manufacturing
	Scrap metal	Metal recycling facility or reused on site	Off site to metal recycler
	Oil drums	Reused or returned	Off site to drum re-conditioner



Waste Management Plan – Porta Products~~Australian Panels~~, Oberon

Waste Category	Source	Management	Disposal
	Sludge (from WTP)	Stored on site	Fuel in heat plants
Liquid waste	Waste oil	Cleanaway	Off-site disposal by licenced contractor
	Brine (from WTP)	captured in production process	As detailed in EMS0006 <i>Surface Water Management Plan</i>
Hazardous waste	Chemical containers	Recycled, reused or disposed	Cleaned, cut up or crushed and sent to Bathurst Regional Council Waste Management Centre
Special waste	Asbestos waste	Asbestos register	Off-site disposal by licenced contractor
	Waste tyres (any used, rejected or unwanted tyres including shredded or tyre pieces)	Tyres collected and stored on site for disposal as required	Off-site disposal by licenced contractor

4.5 Waste Storage Areas

Designated waste storage areas are provided at various locations around the facility as follows:

- Paper treater building;
- Board offcuts skip bins in various locations;
- Metal recycling skip bins at various locations;
- Small general waste bins throughout the facility; and
- Large general waste skip bin.

4.6 Waste Minimisation and Avoidance

~~Australian Panels~~The Development aims is to avoid and reduce waste wherever possible. ~~Australian Panels~~Porta Products has implemented a waste minimisation program by:

- Waste monitoring and tracking to enable the Development to account for trends in waste generation and set targets for reduction where possible;
- Incorporating information on waste classification and disposal into personnel training and communication material;
- Provision and clear identification of separate waste stream disposal bins and/or locations; and
- Discussion of opportunities for waste minimisation during staff and contractor meetings.

4.7 Waste Receipt and Handling On-Site

As described in Section 2.4 of this Plan, EPL 3035 allows specified waste to be received at the premises and stipulates use of that waste at the facility.

Each waste identified as *General or Specific exempted waste* in Section 2.4 must be managed in accordance with the particular resource recovery exemption as issued by the NSW EPA.

5 Incidents and Complaints Management

5.1 Incidents

Any environmental incident relating to waste management will be managed in accordance with the procedures in EMS0001 Operational Environmental Management Plan (OEMP).

5.2 Complaints

Community complaints will be managed in accordance with the procedures in EMS0001 Operational Environmental Management Plan (OEMP).

5.3 Non-Compliances

In the event it is determined that a non-compliance with waste legislation has occurred, notification procedures will be as per EMS0001 Operational Environmental Management Plan (OEMP).

5.4 Contingency Planning

If any unclassified waste material is encountered, it is to be classified in accordance with the NSW EPA *Waste Classification Guideline* prior to disposal off site by a licenced waste contractor to a licenced waste facility.

Any emergency involving the generation of waste is to be managed in accordance with the ~~Porta Products~~~~Australian Panels~~ *Emergency Response Plan*.

6 Monitoring and Review

6.1 Inspections

The Yard Supervisor is responsible for managing waste on a daily basis. The Yard Supervisor undertakes daily inspections and arranges weekly disposal of waste to landfill, and other collections as required.

Regular inspection of waste storage facilities is also undertaken as part of routine environmental inspections.

6.2 Waste Tracking

Waste generated by ~~Australian Panels~~~~The Development~~ is weighed by either the licenced waste disposal contractor or receiving waste management facility. Oberon Council historically received waste based on a cubic metre volume however installed weighbridges in 2025 and now invoice in tonnage. Bathurst Regional Council Waste Management Centre records waste received in tonnage. The following details are recorded:

- Amount and classification of waste transported;
- Date transported;
- Truck registration; and
- Name and location of the receiving waste facility.

~~Australian Panels~~~~The Development~~ undertakes a review of waste management data on an annual basis and reports the findings in the Annual Review report.

6.3 Documentation and Record Keeping

~~Australian Panels~~~~The Development~~ retains all records of waste disposal for traceability, including:

- Waste receipts; and
- Waste Transfer Certificates.

Records relating to waste disposal are kept for a minimum of 4 years.

6.4 Reporting

Relevant information relating to waste management will be reported by ~~the Australian Panels~~~~as~~~~The Development~~ as follows:

- Annual Review. A copy of the Annual Review is sent to relevant stakeholders, including DPE, EPA and Oberon Council and is available on the ~~Australian Panels~~~~Porta Products website~~.

6.5 Review and Auditing of this Plan

In accordance with Development Consent SSD 7016 Condition C10, this WMP will be reviewed and if necessary revised within 3 months of an:

- Approval of a modification;
- Submission of an incident report under Condition C13;
- Approval of an Annual Review under Condition C11; or
- Completion of an audit under Condition C15.

Revisions to the WMP will be submitted to the Secretary DPE for approval.